

SAFETY DATA SHEET CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Supplier Cleenol Group Ltd

Neville House Beaumont Road

Banbury

Oxon OX16 1RB

UK

Tel: +44 (0)1295 251721 Fax: +44 (0)1295 269561 sales@cleenol.co.uk

Manufacturer Cleenol Group Ltd

Neville House Beaumont Road

Banbury

Oxon OX16 1RB

UK

Tel: +44 (0)1295 251721 Fax: +44 (0)1295 269561 sales@cleenol.co.uk

1.4. Emergency telephone number

Emergency telephone Poisons Information Specialist

National Poisons Information Service

Birmingham B18 7QH

Tel: 0121 507 5122

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Eye Dam. 1 - H318

Environmental hazards Not Classified

Classification (67/548/EEC or Xi;R36.

1999/45/EC)

CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H318 Causes serious eye damage.

Precautionary statements P280 Wear protective gloves.

P280 Wear eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

Contains FATTY ALCOHOL ETHOXYLATE

Detergent labelling < 5% amphoteric surfactants, Contains BRONOPOL (INN)

2.3. Other hazards

Other Hazards None

SECTION 3: Composition/information on ingredients

3.2. Mixtures

1-METHOXY-2-PROPANOL 5-10%

CAS number: 107-98-2 EC number: 203-539-1

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 3 - H226 R10 R67

STOT SE 3 - H336 STOT SE 3 - H336

FATTY ALCOHOL ETHOXYLATE 5-10%

CAS number: 160901-19-9

Classification Classification (67/548/EEC or 1999/45/EC)

Eye Dam. 1 - H318 Xn;R22. Xi;R41.

Acute Tox. 4 - H302

PROPAN-2-OL 1-5%

CAS number: 67-63-0 EC number: 200-661-7 REACH registration number: 01-

2119457558-25-0000

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336 STOT SE 3 - H336 Revision date: 22/01/2016 Revision: 10 Supersedes date: 25/09/2015

CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

<1% **BRONOPOL (INN)**

CAS number: 52-51-7 EC number: 200-143-0

M factor (Acute) = 10

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn;R21/22 Xi;R37/38,R41 N;R50

Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335 STOT SE 3 - H335 Aquatic Acute 1 - H400

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Rinse nose and mouth with water. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation May cause respiratory irritation.

Ingestion May cause irritation.

Skin contact May cause skin irritation. Eye contact May cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments Seek medical attention if irritation or symptoms persist. Symptomatic treatment

SECTION 5: Firefighting measures

5.1. Extinguishing media

The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire. Suitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards Burning may produce irritating, toxic and obnoxious fumes.

Oxides of Carbon, Nitrogen and Sulphur.

5.3. Advice for firefighters

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

for firefighters clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections See section 3,8 & 13 for further information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in

the original container.

Storage class Chemical storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

1-METHOXY-2-PROPANOL

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m3(Sk)

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment





Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Revision date: 22/01/2016 Revision: 10 Supersedes date: 25/09/2015

CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

Hygiene measures Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes

contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat,

drink or smoke.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Green.

Odour Characteristic.

pH 6-8

Initial boiling point and range 100°C @ 760 mm Hg

Relative density 1.002 @ 20C°C

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

None known.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid None known.

10.6. Hazardous decomposition products

Hazardous decomposition

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 7,142.85714286

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed.

Skin contact Liquid may irritate skin.

Eye contact Irritating to eyes.

Revision date: 22/01/2016 Revision: 10 Supersedes date: 25/09/2015

CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity The product is not believed to present a hazard due to its physical nature.

12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Not known.

12.4. Mobility in soil

Mobility The product is soluble in water.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the Disposal methods

local Waste Disposal Authority.

SECTION 14: Transport information

Road transport notes Not classified. Not classified. Rail transport notes Not classified. Sea transport notes Not classified.

14.1. UN number

Air transport notes

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

CLEENOL LIFT ORIGINAL MULTIPURPOSE CLEANER

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Safety Data Sheets for Substances and Preparations

Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 22/01/2016

Revision 10

Supersedes date 25/09/2015

SDS number D210

Risk phrases in full R10 Flammable.

R11 Highly flammable. R22 Harmful if swallowed. R36 Irritating to eyes.

R41 Risk of serious damage to eyes.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.